



# WD-40<sup>®</sup>



## MATERIAL SAFETY DATA SHEET

### I. PRODUCT IDENTIFICATION

Manufacturer:	WD-40 Company	Telephone:	
Address:	1061 Cudahy Place (92110) P.O. Box 80607 San Diego, California 92138-0607	Emergency only:	1-(800) 424-9300 (CHEMTREC)
		Information:	(619) 275-1400
		Chemical Name:	Organic Mixture
		Trade Name:	WD-40 Aerosol

### II. HAZARDOUS INGREDIENTS

Chemical Name	CAS Number	%	Exposure Limit ACGIH/OSHA
Aliphatic Petroleum Distillates	8052-41-3	45-50	100 ppm PEL
Petroleum Base Oil	64742-65-0	15-25	5 mg/M <sup>3</sup> TWA (mist)
LVP Hydrocarbon Fluid	64742-47-8	12-18	1200 mg/M <sup>3</sup> TWA
Carbon Dioxide	124-38-9	2-3	5000 ppm PEL
Non-hazardous Ingredients		< 10	

### III. PHYSICAL DATA

Boiling Point:	323°F (minimum)	Evaporation Rate:	Not determined
Vapor Density (air=1):	Greater than 1	Vapor Pressure:	110 ±5 PSI @ 70°F
Solubility in Water:	insoluble	Appearance:	Light amber
Specific Gravity (H <sub>2</sub> O=1):	0.817 @ 72°F	Odor:	Characteristic odor
Percent Volatile (volume):	74%	VOC:	412 grams/liter (49.5%)

### IV. FIRE AND EXPLOSION

Flash Point:	131°F Tag Closed Cup
Flammable Limits:	(Solvent Portion) [Lel] 1.0% [Uel] 6.0%
Extinguishing Media:	CO <sub>2</sub> , Dry Chemical, Foam.
Special Fire Fighting Procedures:	Contents Under Pressure
Unusual Fire and Explosion Hazards:	FLAMMABLE - U.F.C. level 3 AEROSOL

### V. HEALTH HAZARD / ROUTE(S) OF ENTRY

<b>Threshold Limit Value</b>	Aliphatic Petroleum Distillates (Stoddard Solvent) lowest TLV (ACGIH 100 ppm.)
<b>Symptoms of Overexposure</b>	
<b>Inhalation (Breathing):</b>	May cause anesthesia, headache, dizziness, nausea and upper respiratory irritation.
<b>Skin contact:</b>	May cause drying of skin and/or irritation.
<b>Eye contact:</b>	May cause irritation, tearing and redness.
<b>Ingestion (Swallowed):</b>	May caused irritation, nausea, vomiting and diarrhea.
<b>First Aid Emergency Procedures</b>	
<b>Ingestion (Swallowed):</b>	Do not induce vomiting, seek medical attention.
<b>Eye Contact:</b>	Immediately flush eyes with large amounts of water for 15 minutes.
<b>Skin Contact:</b>	Wash with soap and water.
<b>Inhalation (Breathing):</b>	Remove to fresh air. Give artificial respiration if necessary. If breathing is difficult, give oxygen.
	Pre-existing medical conditions such as eye, skin and respiratory disorders may be aggravated by exposure.
<b>DANGER!</b>	
<b>Aspiration Hazard:</b>	If swallowed, can enter lungs and may cause chemical pneumonitis. Do not induce vomiting. Call Physician immediately.
<b>Suspected Cancer Agent</b>	The components in this mixture have been found to be noncarcinogenic by NTP, IARC and OSHA
Yes___ No_X	

## VI. REACTIVITY DATA

Stability:	Stable <u>  X  </u>	Unstable <u>      </u>
Conditions to avoid:	NA	
Incompatibility:	Strong oxidizing agents	
Hazardous decomposition products:	Thermal decomposition may yield carbon monoxide and/or carbon dioxide.	
Hazardous polymerization:	May occur <u>      </u>	Will not occur <u>  X  </u>

## VII. SPILL OR LEAK PROCEDURES

### Spill Response Procedures

Spill unlikely from aerosol cans. Leaking cans should be placed in plastic bag or open pail until pressure has dissipated.

### Waste Disposal Method

Empty aerosol cans should not be punctured or incinerated; bury in land fill. Liquid should be incinerated or buried in land fill. Dispose of in accordance with local, state and federal regulations.

## VIII. SPECIAL HANDLING INFORMATION

Ventilation:	Sufficient to keep solvent vapor less than TLV.
Respiratory Protection:	Advised when concentrations exceed TLV.
Protective Gloves:	Advised to prevent possible skin irritation.
Eye Protection:	Approved eye protections to safeguard against potential eye contact, irritation or injury.
Other Protective Equipment:	None required.

## IX. SPECIAL PRECAUTIONS

Keep from sources of ignition. Avoid excessive inhalation of spray particles, do not take internally. Do not puncture, incinerate or store container above 120°F. Exposure to heat may cause bursting. Keep can away from electrical current or battery terminals. Electrical arcing can cause burn-through (puncture) which may result in flash fire, causing serious injury. Keep from children.

## X. TRANSPORTATION DATA (49 CFR 172.101)

### Domestic Surface

Description:	Consumer Commodity
Hazard Class:	ORM-D
ID No:	None
Label Required:	Consumer commodity (ORM-D)

## XI. REGULATORY INFORMATION

All ingredients for this product are listed on the TSCA inventory.

SARA Title III chemicals:	None
California Prop 65 chemicals:	None
CERCLA reportable quantity:	None
RCRA hazardous waste no:	D001 (Ignitable)

SIGNATURE: Peter Fougner  TITLE:                      Director of Global Quality Assurance                     

REVISION DATE:                      December, 2004                      SUPERSEDES:                      November, 2003                     

NA: Not applicable    NDA: No data available                      < = Less than    > = More than

We believe the statements, technical information and recommendations contained herein are reliable. However, the data is provided without warranty, expressed or implied. It is the user's responsibility both to determine safe conditions for use of this product and assume loss, damage or expense, direct or consequential, arising from its use. Before using product, read label.