



The MSDS format adheres to the standards and regulatory requirements of the United States and may not meet regulatory requirements in other countries.

DuPont  
Material Safety Data Sheet

Page 1

-----  
"StoneTech" Professional Oil Stain Remover  
6474CR Revised 18-JUL-2005  
-----

-----  
CHEMICAL PRODUCT/COMPANY IDENTIFICATION  
-----

Company Identification

MANUFACTURER/DISTRIBUTOR

StoneTech Professional, Inc.  
370 North Wiget Lane  
Suite 200  
Walnut Creek  
California  
94598

PHONE NUMBERS

Product Information : 800-441-7515/Outside US: 302-774-1000  
Transport Emergency : CHEMTREC: 800-424-9300/Outside US:  
703-527-3887  
Medical Emergency : 800-441-3637/Outside US: 302-774-1000

-----  
COMPOSITION/INFORMATION ON INGREDIENTS  
-----

Components

Material	CAS Number	%
d-Limonene	5989-27-5	<50
Calcium Carbonate	1317-65-3	<50
Alkyl Ammonium Bentonite	68953-58-2	
Alkyl Ammonium Montmorillonite	68911-87-5	
Aliphatic Hydrocarbons		
Isopropyl Alcohol (Isopropanol)	67-63-0	

-----  
HAZARDS IDENTIFICATION  
-----

Potential Health Effects

Inhalation: Excessive exposure may cause respiratory irritation.

Skin Contact: May cause skin irritation.

Eye Contact: May cause moderate eye irritation.

Ingestion: May be harmful if swallowed. May cause gastrointestinal irritation with injury.

Carcinogenicity Information

None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, OSHA or ACGIH as a carcinogen.

-----  
FIRST AID MEASURES  
-----

## First Aid

## INHALATION

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

## SKIN CONTACT

Flush skin with water after contact. Wash contaminated clothing before reuse.

## EYE CONTACT

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Call a physician.

## INGESTION

If swallowed, do not induce vomiting. Immediately give 2 glasses of water. Never give anything by mouth to an unconscious person. Call a physician.

## Notes to Physicians

Activated charcoal mixture may be beneficial. Suspend 50 g activated charcoal in 400 mL water and mix well. Administer 5 mL/kg, or 350 mL for an average adult.

-----  
FIRE FIGHTING MEASURES  
-----

## Flammable Properties

Flash Point : 120 F (49 C)  
Method : Closed Cup.

Combustible liquid.

## Extinguishing Media

Use media appropriate for surrounding material.

## Fire Fighting Instructions

Evacuate personnel to a safe area. Wear self-contained breathing apparatus (SCBA) and full protective equipment.

-----  
ACCIDENTAL RELEASE MEASURES  
-----

## Safeguards (Personnel)

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean-up.

## Initial Containment

Dike spill.

## Spill Clean Up

Dispose of in an approved container.

-----  
HANDLING AND STORAGE  
-----

## Handling (Personnel)

Avoid inhalation. Avoid contact with eyes, skin or clothing. Wash thoroughly after handling. Wash clothing after use.

## Handling (Physical Aspects)

Keep container tightly closed.

## Storage

Store in a cool, dry place.

Avoid freezing or extended storage in high temperatures.

-----  
EXPOSURE CONTROLS/PERSONAL PROTECTION  
-----

## Engineering Controls

Use only with adequate ventilation.

## Personal Protective Equipment

## EYE/FACE PROTECTION

Wear safety glasses, or where splash potential exists wear chemical splash goggles.

## RESPIRATORS

Where the potential exists for airborne exposure, wear NIOSH approved respiratory protection.

## PROTECTIVE CLOTHING



## (STABILITY AND REACTIVITY - Continued)

## Polymerization

-----  
DISPOSAL CONSIDERATIONS  
-----

## Waste Disposal

Treatment, storage, transportation, and disposal must be in accordance with applicable Federal, State/Provincial, and Local regulations.

-----  
TRANSPORTATION INFORMATION  
-----

## # Shipping Information

## DOT

Not regulated by DOT in packages with a capacity of less than 119 gallons.

## IMDG

For 2 oz. and 1 pint::

Proper Shipping Name,: Hydrocarbon Liquid, N.O.S.  
Hazard Class,: 3  
UN Number,: 3295  
Packing Group,: III  
Label ,,: Flammable Liquid  
Special Instructions,: Limited Quantity

## IATA

For 2 oz. and 1 pint:

Proper Shipping Name,: Consumer Commodity  
Hazard Class,: 9  
UN Number,: ID 8000  
Packing Group,:  
Label ,,: Miscellaneous

-----  
REGULATORY INFORMATION  
-----

## U.S. Federal Regulations

TSCA Inventory Status : Listed.

(Continued)

---

The data in this Material Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.

# Indicates updated section.

This information is based upon technical information believed to be reliable. It is subject to revision as additional knowledge and experience is gained.

End of MSDS